

## Stainless Steel Pallet Tank Series

### Features :

- ※ Raw material containers are made of stainless steel.
- ※ Likeable appearance with great durability
- ※ With wheels attached to the bottom, the pallet tanks can be conveniently moved around to meet your needs.
- ※ The window on the container allows you to observe and check the production process in a safe fashion.

Model: KA-04

50 kg tank

Features: This stainless steel pallet tank is rectangular in shape with a uncovered opening which places no restrictions on the volume or quantity of raw materials.



Model: KA-04-T

50kg pallet tank

Features: The input-opening of this rectangular pallet tank is well-equipped with a system which controls the input volume at specified points of time (on a condition that a SML loader, SML-820P must be installed.) This pallet tank gives alarm signals when input materials run out.



### Specifications

(Following is for ref. use)

Model	capacity (kg)	Dimension (mm)			Weight (kg)
		W	D	H	
KA-04	50	500	500	1050	10
KA-05	100	600	600	1100	15
KA-04-R	50	Dia 500		1000	10
KA-05-R	100	Dia 600		1100	15
KA-04-T	50	500	500	1100	12
KA-05-T	100	600	600	1200	17
KA-04-AT	50	500	500	1600	15
KA-05-AT	100	600	600	1700	20

Model: KA-04-R

50 kg pallet tank

Features: This stainless steel pallet tank is cylindrical in shape with a uncovered opening which places no restrictions on the volume or quantity of raw materials.



Model : KA-04-AT

A 50kg pallet tank

Features: This rectangular pallet tank is equipped with two separated containers, one for raw materials and the other for sprues, giving you easy control over the proportion of raw materials to sprues, and giving you the choice of producing either one of them. (on a condition that a SML Loader of the SML-820 G/P model and a WA crusher of the WA-XX model must be installed.) Raw materials must be inputted into the pallet tank manually. Sprues are delivered to the KA-XX-AT pallet tank from the Loader by SML-820. The The sprues' container is equipped with an alarm system which gives signals under an overloading condition.





### Level Pads Specification



JSW Hydraulic Machine (J-EIII)			JSW Electric Machine (J-ELIII)		
Machine Model	Applicable	Quantity	Machine Model	Applicable	Quantity
J50E	KM140 x ? 8	8 PC	J35EL	KM140 x ? 8	8 PC
J75 ~J150E	KM140 x ? 8	10 PC	J55 ~ J180EL	KM140 x ? 8	10 PC
J220E	KM190 x ? 2	10 PC	J220EL	KM190 x ? 2	10 PC
J280 ~J450E	KM190 x ? 4	10PC	J280 ~ J450EL	KM190 x ? 4	10 PC

### Hopper Magnetic Specification



Model	Magnet Quantity	Highest Used Temperature	Dimension (mm)	Applicable
MF - 7	7	200°C	180 x 200 x 80	12 - 25 kgs
MF - 9	9	200°C	230 x 240 x 80	50 - 200 kgs

### Mold Clamps

#### Specification

Model	Dia. Of bolt(mm)	L	W	H	Net Weight (kg)	Applicable Injection Molding Machine
RC-12	12	100	38	22	0.6	J35 Ton
RC-16	16	125	45	25	0.9	J55 - 280 Ton
RC-20	20	135	55	38	1.6	J350 - 550 Ton
YC-16	16	125	55	30	0.8	J55 - 280 Ton
YC-20	20	153	68	40	1.3	J350 - 550 Ton

#### YC Model



#### Mold Clamps

#### RC Model



### Mixer

Trait:

1. Stirring blades are installed at a reflex angle, bring about a faster blending speed.
2. The mixing tank tilts at 90 degrees, facilitating the removal of products in a smooth and fast fashion.
3. Well-equipped with a **gear box** at a reduced speed, this mixer gives guarantees of excellent quality.
4. Equipped with a timer, this mixer gives you easy control over the operation duration ranging from 1 to 30 minutes.



Blades of Horizontal Mixer

#### Mixer Specification

Model	Power	Mixed Ability
HMS-100	2.2 kW	100 kgs
HMS-150	4 kW	150 kgs
HMS-200	4 kW	200 kgs



## WIN-BOX Foldable Plastic Boxes

- ※ Made of high impact PP plastic material
- ※ Used by various large established factories and businesses.
- ※ Any sizes available to cater to your specific needs.
- ※ Space-saving, foldable for storage purpose
- ※ Excellent to serve goods distribution and products transportation purposes.
- ※ Damaged components can be replaced
- ※ No metal components are attached to the plastic boxes.
- ※ . Weight capacity reaches 20 kg.
- ※ The weight lighter than a regular plastic box, these foldable plastic boxes bring you much convenience.



Before folded



After folded

### R Type (Under 20KG)

Specification Model	Outside Dimension(mm)			Inside Dimension (mm)			Capacity (L)	Weight (kg)	Highness After Fold (mm)	HK\$ Unit Price 300-500Pc	HK\$ Unit Price 500 PC or Above
	(L)	(W)	(H)	(L)	(W)	(H)					
R0017-01	565	415	230	503	363	217	40	2.2	58	50	45
R0017-02	604	490	335	494	450	320	71	3.4	75	55	50
R0017-03	604	493	370	550	450	350	87	3.5	75	60	55
R0017-04	660	600	588	603	560	560	189	5.5	85	120	115

### LT Type (Under 20KG)

Specification Model	outside Dimension(mm)			Inside Dimension (mm)			Capacity (L)	Weight (kg)	Highness after folded (mm)	HK\$ Unit Price 300-500Pc	HK\$ Unit Price 500 PC or Above
	(L)	(W)	(H)	(L)	(W)	(H)					
LT-JX-11	610	510	350	550	460	335	85	3.5	105	60	55
LT-JX-12	550	375	285	450	335	273	41	2.6	65	50	45
LT-JX-13	550	375	178	450	335	170	26	1.8	65	45	40

Lead Time : To Be Delivered 15 Days After Signed Contract

Payment : To Be Paid by Hong Kong Cheque After Delivery

Remarks : 1. Delivery Is Not Included Under 300 PC Order.

2.The Price Included the Delivery To Shenzhen & Dongguan Area Only

3. No China Mainland Invoice Included.

Unit 02,15/F.,Wing Hing Ind. Bldg, No.83-93 Chai Wan Kok St., Tsuen Wan, H. K.

Tel : (852) 2402 8113, 2402 8133

Fax.: (852) 2402 8878